Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources					
Supplier's name	or trade mark:	HAY			
Supplier's addre	ess: Helle Kabels,	, Havnen 1, 8700 Ho	orsens, DK		
Model identifier	r: PC, 410467				
Type of light sou	ırce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type		Integrated LED			
(or other electric interface)					
Mains or non-m	ains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable	light source:	No	Envelope:	-	
High luminance	light source:	No			
Anti-glare shield	:	No	Dimmable:	Yes	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	G	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		490 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), expressed in W		5,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83	
Outer	Height	550	Spectral power	See image	
dimensions	Width	140	distribution in the	in last page	
without	Depth	500		Page 1 / 3	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,427			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	8	Survival factor	0,90			
the lumen maintenance factor	0,98					

(a)'-': not applicable; (b)'-': not applicable;

