

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** FERMOB

**Supplier's address:** SERVICE RELATION CLIENT, PARC ACTIVAL, 01140 THOISSEY, FR

**Model identifier:** 3612-BALAD-LAMPE H.25 CM

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Diffuseur polyéthylène		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	No

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	1	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	40 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200 or 4 000 or 6 500
On-mode power ( $P_{on}$ ), expressed in W	0,5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		


separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,496
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	22	Survival factor	1,00
the lumen maintenance factor	1,00		

(a): not applicable;

(b): not applicable;


**Attachment No. 1: Photometric test record of one lamp at initial measurement**  
**For Model No.: H25(2200K)**

**Photometric test record of one lamp at initial measurement**



**Attachment No. 1: Photometric test record of one lamp at initial measurement**  
**For Model No.: H25(4000K)**

**Photometric test record of one lamp at initial measurement**



**Attachment No. 1: Photometric test record of one lamp at initial measurement**  
**For Model No.: H25(6500K)**

**Photometric test record of one lamp at initial measurement**

