## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: UMAGE	
--------------------------------------	--

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2232 (light-source)

_	•		
Typa	Ot.	light	source:
IVDE	UI.	HEILL	source.

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Spot			
(or other electric interface)	1,3W 0,4A			
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				

Troduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
	mption in on- 100 h), rounded st integer	2	Energy efficiency class	F	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	125 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pressed in W	oower (P <sub>on</sub> ),	1,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
for CLS, expre	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82	
Outer	Height	23	Spectral power	See image	
dimensions	Width	23	distribution in the	in last page	
without	Depth	19	1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity	0,444	
		coordinates (x and y)	0,414	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	3	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

