Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mar	k: UMAGE
------------------------------	----------

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2424 (light-source)

Type	οf	light	SOLI	rce.
IVDC	vı	HIGHL	JUU	ı cc.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Custom LED PCB 19,7V DC 700mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
	General product parameters:			
Energy consur mode (kWh/10 up to the neare	00 h), rounded	14	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	2 308 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P _{on}), ex-	13,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84
Outer dimen-	Height	410	Spectral power dis-	See image
sions without	Width	410	tribution in the	in last page
separate con- trol gear, light-	Depth	1	range 250 nm to 800 nm, at full-load	

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,437
		nates (x and y)	0,400
Parameters for LED and OLED light sources:			
R9 colour rendering index value	14	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

